

E-TYPE OUTLINE SPECIFICATION

Lift type	Independence Steplift
Travel	To maximum 1000mm
Landings	2
Safe working load	250 kgs
Platform size	1100mm W x 1400mm L
External size	1355mm x 1955mm L , including ramp
Base requirements	Flat surface 1400mm W x 2000mm L minimum, must be level and central to cut out position, no pit required
Gate	Manual interlocked gate with is included
Electrical supply	240v 50hz single phase earthed
Motor	1.1 kW, 4.7 amp - starting current 18 amp
Speed	0.1m/sec
Platform controls	Automatic or hold-to-run & emergency stop on platform console
Landing controls	Call buttons at each landing with isolation key switch
Drive system	Motor driven electro-hydraulic - scissor action frame with battery backup
Duty cycle	15 cycles per hour (max)
Standard finish	Aluminum platform in RAL 7035 white gray & stainless steel handrails, platform stanchions in RAL 7012 dark gray Glass or aluminum side panels in RAL 7012 dark gray. Aluminum gate with glass or aluminum insert in RAL 7012 dark gray Upper & lower call stations
Flooring	Non-slip rubber
Compliance	AS1735:14
Installation time	1 day
Safety features	Standard safety features with pressure sensitive switches and bellows to protect from entry underneath the lift, access and safety ramp
Warranty	12 month warranty